



ALUMAX

BATH ENCLOSURES

by Sapa

391c StikStall

Shower Door-Frameless

Tel: 800-643-1514
Fax: 870-234-3181

www.alumaxbath.com

Product Features

Available in standard and custom configuration
Tempered safety glass
Door has continuous extruded ball and socket hinge that is integral to the hinge rail jamb
Hinge assembly has a molded bushing attached at the top and bottom of door panel

Metal Cuts

SC-505 header = Unit width
SC-505A curb = Unit width
SC-506 head and curb fill = Glass width + 1 3/16"
SC-508 wall jamb = Unit ht. - 3/4
SC-511 180° post = Unit ht. - 3/4
SC-649 hinge jamb = Unit ht. - 2
SC-651 hinge rail = Unit ht. - 3 1/8
SC-552 strike jamb = Unit ht. - 2
SC-558 bottom rail = Door glass width - 7/8
SC-589 drip rail = SC-558 bottom rail + 1 1/4"

Options

Glass patterns
Finish

Calculations

Maximum allowable width of unit = 72
Maximum allowable height of unit = 84

Glass Size

Door glass width as determined
Door glass ht. = Unit ht. - 3 5/8"
Panel glass width = Unit width - door glass width - 4
Panel glass ht. = Unit ht. - 1



391c Parts List

- A. 1 Curb (with weep slots)
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 2 Plastic Setting Blocks
- F. 1 Fixed Glass Panel
- G. 1 180° Post
- H. 1 Header
- J. 12 #8 x 1/4 Truss Head Screws
- K. 1 Strike Jamb with Magnet
- L. 1 Glazed Door Panel
- M. 2 Snap-in Fillers
- N. 1 Handle Vinyl
- P. 1 Pull Handle
- Q. 1 Drip Rail
- R. 2 Drip Plugs
- S. 1 Tapered Drip Vinyl
- T. 1 Roll of Double Stick Tape
- V. 1 #6 x 3/8" Pan Head Screws
- W. 1 Bottom Rail
- X. 1 Rail End Cap
- Y. 2 Pcs. Horz. Glazing Vinyl (72)
- Z. 4 Pcs. Vert. Glazing Vinyl (72)

