



ALUMAX

BATH ENCLOSURES

by Sapa

540/550 Slider Shower Door-Framed

Tel: 800-643-1514
Fax: 870-234-3181

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Adjustable sealed heavy duty ball bearing rollers
- Up and down adjustment of panels is $\pm .156$
- Safety tee-lock wall jamb to header connection
- Molded jamb bumpers with concealed fasteners
- Molded nylon panel guide of sufficient height to prevent the accidental dislodging of interior panel

Calculations

Maximum allowable width of unit = 72
Maximum allowable height of unit = 72

Glass Size

Width = (Unit Width \div 2) - 1 3/8
Height = Unit Ht. - 3 7/8

Metal Cuts

- SC-583 header = Unit width - 1/16
- SC-585 side rail = Unit ht. - 2 3/8
- SC-586 wall jamb = Unit ht. - 1 7/16
- SC-600 top rail = (Unit width \div 2) + 1/8
- SC-601 bottom rail = (Unit width \div 2) + 1/8
- SC-602 tub track = Unit width - 1/4
- SC-634 towel bar = Bottom rail - 2 3/4

540/550 Parts List

- A. 1 Tub Track
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Flat Head Screws
- E. 2 Snap-on Bumpers (with spacer)
- F. 1 Header
- G. 2 #6 x 1/4 Pan Head Screws
- H. 2 Glazed Door Panels
- J. 4 Rollers
- K. 4 #8 x 3/8 Hex Head Screws
- L. 1 Bottom Silencer
- M. 1 Panel Guide
- N. 1 #6 x 3/8 Truss Head Screw
- P. 2 Towel Bar Brackets
- R. 4 #8 x 1/4 Truss Head Screws
- S. 2 Towel Bars
- T. 4 #5 x 1/2 Pan Head Screws
- U. 2 Finger Pulls

