



ALUMAX

BATH ENCLOSURES

by Sapa

791 Pivot StikStall Shower Door-Framed

Tel: 800-643-1514
Fax: 870-234-3181

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Pivot jamba to have a continuous vinyl seal
- Top pivot pin to have safety washer to prevent accidental dislodging of the door

Metal Cuts

- SC-505 header = Unit width
- SC-505A curb = Unit width
- SC-506 head and curb fill = Top and bottom rail + 3/8
- SC-508 wall jamb = Unit ht. - 3/4
- SC-511 180° post = Unit ht. - 3/4
- SC-549 strike rail = Unit ht. - 3 1/8
- SC-552 strike jamb = Unit ht. - 2
- SC-582 pivot rail = Unit ht. - 3 1/8
- SC-552 pivot jamb = Unit ht. - 2
- SC-589 drip rail = SC-899 bottom rail - 11/16
- SC-899 top and bottom rail = Glass width + 1 7/8

791 Parts List

- A. 1 Curb (with weep slots)
- B. 2 Wall Jamba
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 2 Plastic Setting Blocks
- F. 1 Fixed Glass Panel
- G. 1 180° Post
- H. 1 Header
- J. 12 #8 x 1/4 Truss Head Screws
- K. 2 Clear Vinyl Jamb Seals
- L. 1 Glazed Door Panel
- M. 1 Pivot Jamb
- N. 1 Strike Jamb (Magnetic)
- P. 2 Snap-in Fillers
- R. 1 Drip Rail
- S. 2 Drip Plugs
- T. 1 Tapered Drip Vinyl
- V. 1 Roll of Double Stick Tape
- W. 2 #10 x 7/16 Sq. Head Set Screws
- X. 1 Nylon Spacer
- Y. 2 Nylon Pivot Bushings
- AA. 1 Security Washer
- BB. 1 Interior Door Handle
- CC. 1 Exterior Door Handle
- DD. 2 #6 x 1 1/4 Round Head Screws
- EE. 4 Pcs. Vert. Glazing Vinyl (72)
- FF. 2 Pcs. Horiz. Glazing Vinyl (72)

Options

- Towel bar kits
- Glass patterns
- Finish

Calculations

- Maximum allowable width of unit = 72
- Maximum allowable height of unit = 84

Glass Size

- Door glass width as determined
- Door glass ht. = Unit ht. - 5
- Panel glass width = Unit width - door glass width - 5
- Panel glass ht. = Unit ht. - 1

Standard Door Opening Sizes

- 24 5/8 and 29 5/8 width for 68 1/2 unit height
- 24 5/8 and 29 5/8 width for 72 unit height

