



ALUMAX

BATH ENCLOSURES

by Sapa

794c StikStall

Shower Door-Framed

Tel: 800-643-1514
Fax: 870-234-3181

www.alumaxbath.com

Product Features

Available in standard and custom configuration
Tempered safety glass
Door has continuous extruded ball and socket hinge that is integral to the hinge rail jamb
Hinge assembly has a molded bushing attached at the top and bottom of door panel

Metal Cuts

SC-505 header = Centerline dim. + 3/8
SC-505A curb = Centerline dim. + 3/8
SC-505 return header = Centerline dim. + 3/16
SC-505A return curb = Centerline dim. + 3/16
SC-506 head and curb fill = Top and bottom rail + 5/16
SC-508 wall jamb = Unit ht. - 3/4
SC-512 135° post = Unit ht. - 3/4
SC-549 strike rail = Unit ht. - 3 1/8
SC-552 strike jamb = Unit ht. - 2
SC-648 hinge rail = Unit ht. - 3 1/8
SC-649 hinge jamb = Unit ht. - 2
SC-589 drip rail = SC-899 bottom rail - 9/16
SC-899 top and bottom rail = Centerline dim. - 2 5/8

Options

Towel bar kits
Glass patterns
Finish

Calculations

Maximum allowable width of unit = 36 x 36 x 36
Maximum allowable height of unit = 84

Glass Size

Door glass width as determined
Door glass ht. = Unit ht. - 5
Panel glass width = Centerline dim. - 13/16
Panel glass ht. = Unit ht. - 1



Standard Door Opening Sizes

24 9/16 and 29 9/16 width for 68 1/2 unit height
24 9/16 and 29 9/16 width for 72 unit height

794c Parts List

- A. 3 Curb Sections (with weep slots)
- B. 4 135° Anchor Plates
- C. 44 #8 x 1/4 Truss Head Screws
- D. 3 Header Sections
- E. 2 Wall Jamb
- F. 6 Plastic Wall Anchors
- G. 6 #8 x 1 1/2 Truss Head Screws
- H. 4 Plastic Setting Blocks
- J. 2 Fixed Glass Panels
- K. 2 135° Post
- L. 1 Glazed Door Panel
- M. 1 Strike Jamb (Magnetic)
- N. 2 Snap-in Fillers
- P. 1 Drip Rail
- Q. 2 Drip Plugs
- R. 1 Tapered Drip Vinyl
- S. 1 Roll Double Stick Tape
- T. 1 #6 x 3/8 Truss Head Screw
- U. 1 Interior Door Handle
- V. 1 Exterior Door Handle
- W. 2 #6 x 1/8 Round Head Screws
- X. 8 Pcs .Vert. Glazing Vinyl (72)
- Y. 4 Pcs. Horiz. Glazing Vinyl (72)

